



Main

Range of product	Homeline
Product or component type	Loadcentre
[In] rated current	125 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Wall mount
Short-circuit current	10 kA

Complementary

Electrical connection	Lugs
AWG gauge	AWG 6...AWG 2/0 aluminum/copper
Load center type	Main lugs
Number of spaces	12
Number of circuits	24
Number of tandem circuit breakers	12
Network number of phases	1 phase
Cover type	Combination flush/surface cover
Device composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminum busbar
Enclosure material	Welded sheet steel
Cover colour	White
Box number	6

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 indoor)

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
---------------------------------------	---------------------------------

Packing Units

Package 1 Weight	17.81 lb(US) (8.078 kg)
Package 1 Height	5.70 in (14.478 cm)
Package 1 width	16.20 in (41.148 cm)
Package 1 Length	20.60 in (52.324 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile